FAN23 VENTILATING UNITS WITH FILTER


Characteristics	M.U.	FIL25XN0B	FAN23BN0B	FAN23CN0B	FAN23UN0B	FAN23VN0B
Air flow rate	m³/h	-	115/125	115/125	120	120
Power supply	V ~ Hz	-	230 1~ 50-60	115 1~ 50-60	24 V DC	48 V DC
Dimensions HxWxD	mm	250x250x26	250x250x102	250x250x102	250x250x102	250x250x102
Absorbed electric power	W	-	20/19	20/18	7,4	7,7
Max. current	A	-	0,12/0,11	0,21/0,18	0,4	0,16
Over current protection	-	-	Inside motor	Inside motor	Inside motor	Inside motor
Electrical connection	-	-	Faston	Faston	Faston	Faston
Duty cycle	-	-	100%	100%	100%	100%
Temperature limits	°C	-30 +75	-10 +50	-10 +50	-10 +50	-10 +55
Protection level EN60529	-	IP54	IP54	IP54	IP54	IP54
Noise level	dB (A)	-	43/48	43/48	43	43
FAN + FIL capacity	m³/h	-	1xFIL25XN0B: 92/106 1XFIL35XN0B: 101/111		1xFIL25XN0B: 104 1XFIL35XN0B: 111	
Direction of the air flow	-	-	Outside towards the inside Reversible	Outside towards the inside Reversible	Outside towards the inside Reversible	Outside towards the inside Reversible
Filter (Eurovent 4/9)	-	EU3	EU3	EU3	EU3	EU3
Motor support	-	-	Bearings	Bearings	Bearings	Bearings
Conformity	-	CE	CE	CE	CE	CE
Colour	-	RAL 7035 orange peel effect				

Accessories / Options	
Pack of 10 cloth filters for FAN23-25	AAFFN25
Pack of 10 cloth filters for FAN23-25 high filtering capacity	AAFFH25
Pack of 10 cloth filters for FAN35	AAFFN35
Pack of 10 cloth filters for FAN35 high filtering capacity	AAFFH35
0-60°C thermostat, NO 10A	AAFTO12
5-60°C thermostat, change-over contact 10A	AAWTS10
Casing for IP55 protection	C12001229

REMARK : The drilling templates are merely indicative.
Always put in touch with our technical-sales department for further explanation you should need.




Performances




P = Static pressure (Pa)
Q = Air flow rate (m³/h)

FAN23



FIL23



Dimensions **Driling templates**